

Drip Applications

Product Type

Valve StackVSN
 Valve Stack With ReservoirVSRN
 Injector Stack Only.....INJN

Voltage

120 VACA
 220-240 VAC, 50/60HzB
24 VDC (European Version Only)*--see belowC
 24 VDC.....D
 No Solenoid (INJ only)X

Millennium Timer Options {connector timer} *Operating Range*
 Continuous (1) MCT 120V; (2) MCT 240V; (3) MCT 24VDC (2.1 to 200 seconds)
 Continuous (4) MPT 120V; (5) MPT 240V; (6) MPT 24VDC (0.5 to 5 seconds)
 Continuous (7) MCT 120V; (8) MCT 240V; (9) MCT 24VDC (4 to 400 seconds)

Injector Size

Half-Drop InjectorH
 Two-Drop InjectorT

Number Of Injectors

Range from "1" to "8"

Fitting Location

In-Line LocationIL
 Low-Profile LocationLP
 No FittingsXX

Type Of Fitting

(Nylon: 3/16" O.D. Tubing Steel Tube: 1/8" O.D. Tubing)
 Nylon Push-In FittingsNY
 Nylon Compression FittingsNC
 Steel Tube Fittings: Carbon SteelCS
 Steel Tube Fittings: Stainless SteelSS
 No Fittings.....XX

Reservoir Fill Options (Omit for VSN or INJN product)

Manual FillM
 Central FillP
 Manual Fill/High Level SwitchMH
 Central Fill/High Level SwitchPH
{a low-level switch is a standard feature}

VSN A H [Red Grid] IL NY M

* DIN 43650 (LED & Surge Suppressor) solenoid connectors with metric tube fittings.

In-Line Fitting Location



Low-Profile Fitting Location



(Note: product shown above is in the VS configuration. The actual product will not include a pressure regulator, or a air solenoid for nozzle air--it will include only one air solenoid to control the injector cycle rate.)